

# BUMERANG BLT 250



## Pneumatic Line Thrower

The BLT 250 Line Thrower is a pneumatic system which is throws projectiles by power of compressed air. BLT 250 has interchangeable launchers and easy refilling projectiles. Meets the demands of Solas/IMO regulation 74/83 and recognized by RINA, Notified Body No: 0474 (Number: MED088716XTJ. Also approved by USCG (Number: 160.040/EC0474) and similar organizations in other countries as a linethrowing appliances onboard ships.

### PERFORMANCE


Projectile reaches approximately 250 meters. Projectiles only effected from crosswind. Projectile reaches the maximum speed at end of the launcher. Due to aerodynamic structure, wind has the minimum effect on the projectiles.

### SAFETY

Because there is no explosives, it can be threw from and into flammable areas. Two safety features protect the system from false and accidental throwing.

### ECONOMY

All items are reusable. Shelf life is unlimited, if regular maintenance is done by Authorized Service's personnel. Only cost for 4 throws is refilling the cylinder with dry air.



0474 / XXXX




# BUMERANG BLT 250

## Pneumatic Line Thrower

### Technical Info

<i>Weight/Length</i>	<i>Throwing Unit 8,3kg /165cm Projectile 2,1kg /100cm Total Unit 11.2 kg /175cm</i>
<i>Materials</i>	<i>Deep Draw and Extruded Aluminum 6082 T-6Stainless Steel. MS 58 Brass.PVC.ABS</i>
<i>Finish</i>	<i>Hard Anodized, Chrom Nikel Plated</i>
<i>Colour</i>	<i>Black and Yellow</i>
<i>Shooting Chamber Pressure</i>	<i>65 bar</i>
<i>Average Nozzle Velocity</i>	<i>50,6m/s</i>
<i>Maximum Recoil</i>	<i>5400N</i>
<i>Minimum Shots</i>	<i>4 projectiles</i>
<i>Aluminium Air Cylinder</i>	
<i>Pressure</i>	<i>200 bar</i>
<i>Volume</i>	<i>2 Liters</i>
<i>Bag Size</i>	<i>105 x 22 x 20cm</i>
<i>Total Bag Weight</i>	<i>16,5 kg</i>



- 1 BLT 250 Throwing Unit*
- 4 Projectiles for BLT 250*
- 1 Launcher User Manual*

